



S-GHD75-16

October 2016

# SPECIFICATIONS

## 75 ton JEEP DOLLY

### ETNYRE TRIPLE AXLE JEEP DOLLY - 75 TON

Capacity: Proportionate share of up to 75 tons  
Minimum trailer gooseneck clearance radius - 216"  
50" Tractor loaded 5th wheel height  
80" Gooseneck clearance radius  
Telescopic drop legs  
50" Sliding 5th wheel height (loaded)  
66" Sliding 5th wheel  
Ridewell air suspension  
Over-ride chains on three (3) axles  
Manual exhaust valve for air suspension  
8'-0" (96") wide  
Tires - 255/70R 22.5 (H) 16 PR tubeless radials  
Wheels - 8.25 x 22.5 single piece steel disc (white)  
Hubs - Hub piloted with outboard drums

Axles - 22,500# (5/8" wall thickness) with oil bearings  
Brakes - 16 1/2" x 7" full air  
Spring brakes - one (1) axle (center axle)  
Anti-Lock brakes - None  
Automatic slack adjusters  
Mast for cable and hoses  
Jumper cable and hoses  
Lighting - L.E.D. type - rubber mounted - mid turn signal  
Finish - shot blast / epoxy primer / urethane finish  
Air lines - glad hands  
Electrical - 7 way receptacle and plug  
Lash rings - 4 at balance point  
Mud flaps  
Red and white conspicuity markings

