



from 80 to 150 HP

Ø6 in max (stones)

D6 ir

STONE CRUSHER WITH FIXED TOOTH ROTOR.

The STCL is the smallest stone crusher FAE makes. It is extremely versatile thanks to it small dimension and lower weight. This makes it suitable for use in orchards and vineyards where stones can emerge due to soil erosion. An adjustable internal counter-blade allows you to obtain the desired final material size. The hydraulically controlled rear door also helps in determining final product size. This attachment also has a specially mounted gearbox so while it sits in a low position, the PTO shaft still sits at an optimal angle.

| The state of the s | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| | 1 34 |
| WAGNER WIGHT TO THE | Vannia and |
| | (8) |
| | |
| | |
| EAT. | |
| | |

STANDARD EQUIPMENT

PTO shaft with cam clutch

Gearbox with freewheel

Transmission with belts in Poly-Chain® Carbon

Hydraulic rear hood

Flat pressed welded steel counter-blades

Adjustable Hardox® counter-blade

Penetration skids

Enclosed machine body

Inside lateral protection

Dual row protection chains



Possibility to choose Transmission 540 / 1000 rpm

Choice between 540 and 1000 rpm transmission (STC 125)

Adjustable extended 3 point linkage (STCL/ST)

Hydraulic top link

Dozing blade

Grader blade



Adjustable extended 3 point hitch

fits perfectly with any kind of tractor



protects internal components

Adjustable Hardox® counter-blade effectively control the final product size

Penetration skids help the machine to better

penetrate the soil





| MODEL | Engine (HP) | | PTO (rpm) | Working width | Total width | Weight | Max shredding diameter | Max working depth | No. teeth type STCL/3+ |
|-------------|-------------|------|--------------|------------------|-------------|--------|------------------------------|-------------------------|---------------------------|
| | min | max | | (in) | | | (in) | (in) | C/3/SS |
| STCL 100 | 80 | 120* | 540-1000 | 44 | 56 | 2712 | 6 | 6 | 20+4 |
| STCL 125 | 80 | 120* | 540-1000 | 53 | 65 | 2822 | 6 | 6 | 26+4 |
| STCL 150 | 90 | 120* | 540-1000 | 63 | 75 | 3175 | 6 | 6 | 32+4 |
| STCL 175 | 100 | 120* | 540-1000 | 72 | 84 | 3462 | 6 | 6 | 38+4 |
| STCL/DT 175 | 100 | 150 | 1000 | 72 | 84 | 3528 | 6 | 6 | 38+4 |
| STCL/DT 200 | 120 | 150 | 1000 | 81 | 94 | 3858 | 6 | 6 | 42+4 |